

AMENDMENTS TO THE CLAIMS

LISTING OF CLAIMS:

This listing of claims replaces all prior versions, and listings, of claims in the application:

Claims 1 through 32 are cancelled.

Claims 33 through 50 are pending in this application.

33. *(Currently amended)* A pole vibration damping assembly mountable on a vertical ~~stationary~~ non-rotatable pole for damping wind induced first harmonic mode ~~pole~~ vibrations of the pole, said assembly comprising an annular housing including a horizontally oriented first housing component half-portion and a horizontally oriented second housing component half-portion horizontally aligned with the first housing component half-portion and connections connecting the first housing component half-portion to the second housing component half-portion, each housing component half-portion including an inner partial cylinder sleeve having an inner partial cylinder sleeve surface having a lower end portion, a vertical center of curvature and being dimensioned and shaped to fit in a mating manner over, and in facing contact with, an upper end portion of a vertical ~~stationary~~ non-rotatable pole and having an axis approximately coextensive with

the center of curvature of the pole, an outer partial cylinder sleeve positioned outwardly of the inner partial cylinder sleeve surface and having a lower end termination portion and a vertical center of curvature that is coextensive with the center of curvature of the inner partial cylinder sleeve surface, a floor panel extending between lower portions of the inner partial cylinder sleeve surface and the outer partial cylinder sleeve, a plurality of vertical partitioning panels extending vertically upward from the floor panel and extending between the inner partial cylinder sleeve and the outer partial cylinder sleeve to define non-circular damping weight receiving chambers between adjacent partitioning panels and a movable damping weight supported by the floor panel for horizontal rolling movement in each of the damping weight receiving chambers.

34. *(Currently amended)* A pole vibration damping assembly as recited in claim 33, wherein the damping weights are spherical balls and the shape and dimensions of the damping weight receiving chambers are of sufficient ~~dimension~~ to permit rolling movement in any direction of the spherical balls in the respective damping chamber in which each spherical ball is positioned.
35. *(Previously presented)* A pole vibration damping assembly as recited in claim 34, wherein the damping weights are spherical metal balls and the partitioning panels are connected to the inner partial cylinder sleeve and the outer partial cylinder sleeve.
36. *(Previously presented)* A pole vibration damping assembly as recited in claim 33, wherein the damping weights are spherical lead balls.

37. *(Previously presented)* A pole vibration damping assembly as recited in claim 33, wherein the partitioning panels are planar panels.
38. *(Previously presented)* A pole vibration damping assembly as recited in claim 33, wherein the partitioning panels are planar panels oriented in substantially perpendicular manner relative to the floor panel.
39. *(Previously presented)* A pole vibration damping assembly as recited in claim 33, wherein the damping weights are plastic coated spherical metal balls.
40. *(Previously presented)* A pole vibration damping assembly as recited in claim 33, wherein the damping weights are plastic coated spherical metal balls that are coated with polyurethane.
41. *(Currently amended)* A pole vibration damping assembly as recited in claim 33, wherein the first housing component half-portion and the second housing component half-portion are fixedly connected together to cooperatively encircle the pole, each housing component half-portion includes a first planar ~~plate~~ panel extending between a first end portion of the inner partial-cylinder sleeve and a connector lug comprising part of the connection on a first end portion of the outer partial-cylinder sleeve, and a second planar panel extending between a second end portion of the inner partial-cylinder sleeve and a connector lug comprising part of the connection on a second end portion of the outer partial-cylinder sleeve and threaded metal screws comprising part of the connection connecting the connector lug of the second housing component half-portion to provide a rigid housing structure.

42. *(Previously presented)* A pole vibration damping assembly as recited in claim 41, wherein the damping weights are spherical metal balls.
43. *(Previously presented)* A pole vibration damping assembly as recited in claim 41, wherein the damping weights are spherical lead balls.
44. *(Currently amended)* A vibration damping device mountable on a non-rotatable vertical pole for damping wind induced first harmonic mode vibrations comprising a housing mountable on such a pole and including an annular horizontally aligned array of weight receiving chambers solely occupied by ~~ambient air and~~ a spherical ball damping weight and wherein the housing is shaped and dimensioned to encircle and facingly engage such a pole to effect mounting of the device on the pole, and the horizontally aligned weight receiving chambers are separated by planar panels preventing movement of the spherical ball damping weights from one weight receiving chamber to an adjacent weight receiving chamber.
45. *(Previously presented)* A vibration damping device as recited in claim 44, wherein, the spherical ball damping weights are freely rollable in any horizontal direction in their respective weight receiving chamber.
46. *(Previously presented)* A vibration damping device as recited in claim 44, wherein, the damping weights are spherical metal balls.
47. *(Previously presented)* A vibration damping device as recited in claim 44, wherein, the damping weights are spherical lead balls.

48. *(Previously presented)* A vibration damping device as recited in claim 44,
wherein, the damping weights are plastic coated spherical metal balls.
49. *(Previously presented)* A vibration damping device as recited in claim 48,
wherein, the plastic coating is polyurethane.
50. *(Previously presented)* A vibration damping device as recited in claim 44,
wherein the weight receiving chambers are of non-circular configuration.